Auto Weighing/Filling machines

- 1)CJ Series Automatic Granule Linear weigher;
- I. Introduction:
- 1. This is Linear weigher with vibration feeding/gate feeding system, use Touch screen and MCU control system. Be easy for operation and maintain;
- 2. Frame and contact parts be made by 304 S.S;
- 3.Separated Weighing system, be good for small free flow granule products, such as nuts, sugar, rice and seeds, etc.
- 4.Also have the special design feeding system for weighing and filling ice tube, tea leaves, etc.

Model	Scale No.	Weighing Range	Filling speed	Accuracy
CJS200	2 head	20-200g	10-20times/min	
CJS2000	2 head	50-2000g	10-20times/min	
CJF2000	4 head	50-2000g	20-50times/min	
CJS5000	2head	200-5000g	10-20times/min	+/- 0.2%
CJF5000	4 head	200-5000g	20-40times/min	7- 0.2 %
CJD50K-S15	2 head	5-15kg	360times/hour	-
CJD50K-S25	2 head	10-25kg	360times/hour	1
CJD59K-S50	2 head	20-50kg	300times/hour	1

II. Technical Information:

2) ZH Series Automatic Combination Multi-head Weigher For irregular products

I. Introduction:

This is multi-head combination weigher. Including center panel feeder, linear feeder, receive hoppers, weighing hoppers, discharge hopper etc.

It is suitable for high speed weighing of granule, slice, roll or irregular shape products such as candy, seed, jelly, fries, coffee bean, peanut, puffy food, biscuit, chocolate, nut, yogurt, pet food & frozen foods, etc. It is also suitable for weighing small metal and plastic parts;

*Load cell level sensor control material feeding;

*No products Auto pause function can avoid material dropping out during Running; *The single linear feeder amplitude can be auto/manual adjusted will ensure the products easy-flowing with high accuracy;

- * Facility to maximize or minimize the operation angle to the size of the product.
- * Multilanguage control panel, Spanish, Korea, German, French and Arabic, etc.
- * High accuracy and high speed modes can be select..

Options: Dimple Plate/Timing Hopper/Printer/Reject Device

Model	Scale No./Hopper size	Weighing Range	Filling speed	Accuracy
ZH10-1.6L	10 head/1.6L	10-1000g	Max 65time/min	X (0.5)
ZH10-2.5L	10 head/2.5L	10-1000g		
ZH10-5L	10 head/5L	100-3000g	Max 50times/min	X (1)
ZH14-1.6L	14 head/1.6L	10-1500g	May 120haga/min	X (0.5)
ZH14-2.5L	14 head/2.5L	10-1500g	Max120bags/min	
ZH14-5L	14 head/5L	100-3000g	Max 80 times/min	X (1)

II.Technical information:

3)CJSL Series Vertical auger filler for powder

I. Introduction:

This machine equips with Panasonic Servo Motor, level switch and mixture motor automatic filling, controlled by packaging machine. Made by Stainless Steel.

- ⇔ 60L Split hopper for easy clearing;
- ⇒ With level sensor to control the powder automatic feeding;
- Solution ⇒ With servo motor to control the vertical screw feeding in accuracy;
- Siemens PLC & Touch Screen;
- Schneider electronics.
- SPhase motor for hopper agitator;
- Srame & Contact parts be made by 304 S.Steel.

	Hopper size	Weighing Range	Filling speed	Accuracy
CJSL200/Vertical Auger	20L	5-200g	Max 60time/min	+/- 0.5-2g
CJSL2000/Vertical Auger	60L	50-2000g	Max 60times/min	+/- 1-5g

CJSL5000/Vertical Auger	80L	200g-5000g	Max 50times/min	+/- 1-8g
CJL25K/Vertical Auger	90L	5-25kg	2-4times/min	+/10-50g
CJ-WL25/Horizontal twin Auger	90L	5-25kg, 20-50kg	3-6 times/min	+/10-50g

4)CJ-WL Series Horizontal Auger filler;

I.Introduction:

This machine equips with Panasonic Servo Motor, level switch and mixture motor automatic filling, controlled by packaging machine. Made by Stainless Steel. It own advantages as follow:

- 1.60L Split hopper for easy clearing;
- 2.With level sensor to control the powder automatic feeding;
- 3.With servo motor to control the vertical screw feeding in accuracy;
- 4.Siemens PLC & Touch Screen;
- 5.Schneider electronics.
- 6.3Phase motor for hopper agitator;
- 7.Frame & Contact parts be made by 304 S.Steel.

Model/Type	Hopper size	Weighing Range	Filling speed	Accuracy
CJSL200/Vertical Auger	20L	5-200g	Max 60time/min	+/- 0.5-2g
CJSL2000/Vertical Auger	60L	50-2000g	Max 60times/min	+/- 1-5g
CJSL5000/Vertical Auger	80L	200g-5000g	Max 50times/min	+/- 1-8g
CJL25K/Vertical Auger	90L	5-25kg	2-4times/min	+/10-50g
CJ-WL25/Horizontal twin Auger	90L	5-25kg, 20-50kg	3-6 times/min	+/10-50g

II.Technical information: